


CB-XIS20W

1080P True WDR
Network Box Camera



Key Features

- > 1/2.8" Progressive Scan CMOS
- > 50fps/60fps@1080P(1920*1080)
- > Triple Streams, Triple Power Supply
- > Low bitrate, Excellent low light performance
- > WDR, 3D DNR
- > ROI, Defog, HLC, Corridor mode, DIS
- > Auto back focus (ABF)
- > Built-in SD card slot, Max 128GB

Overview

CB-XIS20W is a True WDR box camera that supports H.265 encoding technology and efficient video compression. Being bandwidth, storage and energy saving at the same time, it is designed to enhance any monitoring system and meets the contemporary security needs. Meanwhile, its embedded Video Analytics features such as Perimeter, Virtual Fences, Object left/removed etc, offer high quality surveillance in demanding environments. Equipped with an 1/2.8" Progressive Scan CMOS image sensor and ICR – IR cut filter, it provides an overall excellent and high resolution image quality.

SPECIFICATIONS

CAMERA

Image Sensor	1/2.8" Progressive Scan CMOS
Min. illumination	Color:0.001Lux@(F1.2,AGC ON) / B/W:0.0001Lux@(F1.2,AGC ON)
ICR - IR Cut Filter	Yes
Shutter Speed	1/5-1/20000
Auto Iris	Yes
Wide Dynamic Range	True WDR>120dB
Digital Noise Reduction	2D/3D
Lens Type/Length	No
FOV	No
IR LEDs	N/A
IR Distance	N/A

IMAGE

Video Compression	H.265, H.264, MJPEG
Bit Rate (CBR/VBR)	Stream1: 500kbps~12000kbps Stream2: 100kbps~6000kbps Stream3: 100kbps~3000kbps
Audio Compression	G.711 ,RAW_PCM
Max.Resolution	1080P (1920×1080)
Stream	Stream1:1920×1080/1280×720 @50/60fps Stream2: D1/VGA/640×360/CIF/QVGA @25/30fps Stream3: VGA/CIF/QVGA @25/30fps
Image Setting	Rotate Mode,Saturation,Brightness,Contrast,Sharpness
HLC	Yes
9:16 Corridor Mode	Yes
DIS	Auto
ROI	Yes
Defog	Yes


NETWORK

Protocols	IPv4, 802.1x, HTTP, HTTPS,TCP/IP, UDP/IP, RTSP, DHCP, NTP, RTCP/ RTP, PPPoE, SMTP, DNS, UPnP, FTP, ICMP, IGMP, Unicast and Multicast
Alarm Trigger	Perimeter, Single Virtual Fences, Double Virtual Fences, Loiter, Multi Loiter, Object Left, Object Removed, Abnormal Speed, Converse, Illegal Parking, Signal Bad
RTSP Video	Standard RFC2326, Support Quick-Time / VLC Player
Security	User security authentication, Reset, Hardware WatchDog
Web Language	English, Chinese, Polish, Italian, Portuguese, Spanish
Compatibility	Onvif

INTERFACE

Ethernet	1 Ethernet (10/100 Base-T) RJ-45 Connector
Audio I/O	1ch Audio In,1ch Audio Out, 1 Built-in Mic
Alarm I/O	1ch Alarm In,1ch Alarm Out
RS485	Support
BNC Output	Support
Reset Button	Support
Edge Storage	Micro SD card slot, Max 128GB

DIMENSIONS



CUBITECH LTD

R&D 12 Basepoint Business Centre, Enterprise Close, Christchurch, Dorset, Poole BH23 6NX, UK, T +44 (0) 1202 853237

DISTRIBUTION CENTER 4-6 Kiprou Str., 177 78, Tavros, Athens, Greece | T +30 210 9580887-8, F +30 210 9580885

E. info@cubitech.com | www.cubitech.com