

# CB-BIB2036F

1080P, IR Bullet Mini Camera



## Key Features

- Compact, metal design
- Powerful impact protection due to IK10
- Excellent water protection resistance due to IP66

2.1MP IP66 POE IK10 ONVIF



## Overview

CB-BIB2036F is an IP bullet camera ideal for day & high-powered night time surveillance. This camera is enclosed in a high quality, weatherproof, durable case for outdoor surveillance and can produce a sharp, high quality, color images even in low light environments.

## Specifications

### Camera

Part No	1115036
Image Sensor	1/2.7" Progressive Scan CMOS
Min. illumination	Color 0.2Lux(AGC ON);IR ON 0 Lux
ICR - IR Cut Filter	Yes
Shutter Time	1/1-1/10000
Auto Iris	N/A
Wide Dynamic Range	dWDR
Digital Noise Reduction	2D/3D
Lens Type/ Focal Length	3.6mm, Fixed lens
FOV	94°
IR LEDs	18pcs
IR Distance	15m

### Image

Video Compression	H.265 / H.264 High/Main/Baseline Profile/ MJPEG
Bit Rate (CBR/VBR)	Main stream:500kb-12000kb, Sub stream 100kb-6000kb
Audio Compression	G.711, RAW_PCM
Max.Resolution	1920x1080@30fps
Stream	Stream 1: 1920x1080/1280x720 Stream 2: D1 to QVGA
Image Setting	Rotate Mode, Saturation, Brightness, Contrast, Sharpness
HLC	Yes
DIS	Yes
9:16 Corridor mode	Yes
ROI	Yes
Defog	N/A

### Network

Supported Protocols	IPv4, 802.1x, HTTP, HTTPS, TCP/IP, UDP/IP, RTSP, DHCP, NTP, RTCP/RTP, PPPoE, SMTP, DNS, UPnP, FTP, ICMP, IGMP, Unicast and Multicast
Alarm Trigger	Motion Detection, Network disconnect
RTSP Video	Standard RFC2326, Support QuickTime / VLC Player
Security	User security authentication, Reset, Hardware WatchDog
Web Language	English, Polish, Italian, Portuguese, Spanish, Chinese
Compatibility	Onvif

### Interface

Ethernet	1 Ethernet (10/100 Base-T) RJ-45 Connector
Audio I/O	N/A
Alarm I/O	N/A
RS485	N/A
BNC Output	N/A
Reset Button	N/A
Edge Storage	N/A

### General

Power Supply	DC12V/POE
Power Consumption	2.5W (IR LED OFF), 5W(IR LED ON)
Operating Temperature	Starting Temperature: -10 ~ 50 (14 ~ 122 ) Working Temperature: -20 ~ 50 (-4 ~ 122 )
Operating Humidity	0% - 90% RH
Protection Level	IP66, IK10
Certifications	CE / FCC
Dimensions	φ196.5x62mm
Net Weight	360g

## Dimensions

---

